














COLORIT® Graphics

















COLORIT® is the internationally established brand name for the high-quality program of pigmented stamping foils from KURZ.

COLORIT® 900 series is covers matte colored foils for the graphics industry.

*For exact colours see a physical sample.

*Colour indicator		V 900	VB 900	VL 900	AC 900	TRANS 800	METALLIC	PEARL 90000	
		● = Produced regularly ○ = Not produced regularly							
	K901	○							
	K902	●		○					
	K911N	●	●	●	●				
	K912	●	●	●	●				
	K914N	●	●						
	K916	●							
	K917	●	●						
	K922	○	●						
	K923	●							
	K924A	●	○						
	K925	●	○						

*Colour indicator		V 900	VB 900	VL 900	AC 900	TRANS 800	METALLIC	PEARL 90000	● = Produced regularly ○ = Not produced regularly
	K931	●							
	K932	●	○						
	K933	○							
	K935A	○	○						
	K937	●							
	K941A	●							
	K943	●	○						
	K946	○							
	K948A	○							
	K949	●						TRANSPARENT	
	K960	●	○						
	K961	●	○						
	K962	○							
	K963	●	●						
	K964	●	●	○					
	K965	●	○						

*Colour indicator		V 900	VB 900	VL 900	AC 900	TRANS 800	METALLIC	PEARL 90000	● = Produced regularly ○ = Not produced regularly
	K967	●	○						
	K968	●	●						
	K969	●							
	K970	○							
	K971	○							
	K972N	●							
	K973	●	○						
	K974N	○							
	K975A	●	○	○					
	K976	●	○						
	K977	●							
	K978	●	○						
	K812					●			GLOSSY
	Silver						●		METALLIC
	Bronze						●		METALLIC
	K99015							●	PEARL



ZETATRADE

TFN 08 546 246 00 - MAIL info@zetatrade.se - WEB zetatrade.se

COLORIT® V 900

Versatile matte pigment color foil for book covers and other applications of the graphic industry

Main Characteristics

- excellent adhesion on many different types of surfaces, broad application field
- precise definition
- suitable for fine to medium fine designs
- applicable for paper and cardboard
- surfaces, artificial leather, genuine leather, PVC, coated and laminated cartons, wood etc.

Fields of Application

- book covers,
- envelopes,
- folding cartons,
- labels,
- stationery paper

Stamping Temperature

- 100 - 120 °C / 212 - 248 °F for up-down stamping
 - approx. 150 - 170 °C / 302 - 338 °F for cylinder stamping
-

COLORIT® VB 900

Exceptionally well covering matte pigment foil for book covers made of linen and other fabrics, as well as for paper and cardboard materials with coarse surfaces

Main Characteristics

- excellent covering properties with high abrasion, scratch and rub resistance
- strong adhesion during rounding the spine
- suitable for medium size and large designs on linen, fabrics, grained artificial leather, coarse paper and carton surfaces
- applicable for book spine panels which are over stamped in a subsequent production process

Fields of Application

- book covers,
- envelopes etc.

Stamping Temperature

- approx. 120 °C / 248 °F for up-down stamping
- approx. 150 - 170 °C / 302 - 338 °F for cylinder stamping

COLORIT® VL 900

Matte pigment foil for self-adhesive labels and other substrates of the graphic industry. Very clean definition.

Main Characteristics

- suitable for smooth surfaces, e. g. different label materials
- recommended for fine to very fine designs

Fields of Application

- Self-adhesive labels which are stamped on label stamping machines.

Stamping Temperatures

- 120 - 130 °C / 248 - 266 °F
-

COLORIT® AC 900

Matte pigment color formulation designed for acetate laminated and lacquer coated folding cartons in particular.

Main Characteristics

- suitable for stamping of acetate laminated and lacquer coated surfaces
- high crease resistance
- excellent definition
- suitable for fine to medium fine designs
- perfect covering properties on printed surfaces

Fields of Application

- acetate laminated and lacquer coated substrates

Processing Temperatures

- 110 - 120 °C (230 - 248 °F) for up-down stamping
 - 150 - 170 °C (332 - 338 °F) for cylinder stamping
-

COLORIT® TRANS 800

Glossy pigment foil for the graphic industry

Main Characteristics

- to be used on unprinted, printed and coated paper and cardboard
- suitable for all types of stamping machines in the graphic industry
- recommended for fine to large designs
- good covering properties on matte and coarse surfaces
- very glossy
- very high abrasion and scratch resistance
- good overstampability with LUXOR®/ALUFIN®

Fields of Application

- folding cartons for cosmetic products,
- greeting cards,
- labels,
- advertising material etc.

Stamping Temperature

- 95 - 100 °C for up-down stamping
- 130 - 140 °C for cylinder stamping