



# GEBA 1/A, 1/F, 7

Hand-Operated Hot Stamping Machines



GEBA 1/A



GEBA 1/F



GEBA 7



GEBA 1/A



GEBA 1/F



GEBA 7

## technical dates

	Model GEBA 1/A – Hand-Operated Hot Stamping Machine	Model GEBA 1/F - Hand-Operated Hot Stamping Machine for titles	Model GEBA 7, Execution C + D – Hand-Operated Hot Stamping Machine
<b>Construction:</b>	one-column pillar, table model	C-pillar, table model	C-pillar
<b>Drive:</b>	hand-operated	hand-operated	hand-operated
<b>Stroke of plunger:</b>	28,5 mm	28,5 mm	50 mm
<b>Stamping area:</b>	70 x 90 mm	70 x 90 mm	Execution C: 150 x 210 mm Execution D: 210 x 300 mm
<b>Stamping pressure adjustable:</b>	0-800 kp (8 kN)	0-600 kp (6 kN)	0-4000 kp (40 kN)
<b>Daylight (adjustment of height):</b>	0-180 mm	0-96 mm	0-30 mm
<b>Throat (middle of stamping plate to column/bow):</b>	110 mm	320 mm	175 mm
<b>Temperature regulation:</b>	electronical	electronical	electronically
<b>Working table:</b>	221 mm wide x 230 mm deep, slidable to all sides, fine adjustment from the front	620 x 620 mm, stationary	468 mm wide x 310 mm deep, slidable to all four sides
<b>Foil feeding system:</b>	mechanical, 1-fold from left to right side, with foil rewinding system	hand-operated, running from left to right side with rewinding device	mechanical, 1-fold from left to right, with foil rewinding system
<b>Heating efficiency</b>		320 watts	Execution C: 1400 W Execution D: 2280 W
<b>Standard accessories:</b>	Die-holding plate without locking frame Stroke counter mechanical Height measurement unit, mechanical Galvanized execution	Electrically heated hot-stamping plate 70 x 90 mm Adjustable table limit stop Electrically heated type box for a clamping length of 110 mm for 6,55 and 23,56 mm high types	Die-holding plate without locking frame Die-holding plate with locking frame for 23,56 mm high types Mechanical stroke counter
<b>Colour of machine:</b>			light grey RAL 7035 with yellow RAL 1021
<b>Voltage:</b>	1 phase, 230 volts A.C. 50 Hz, viz. according to voltage of buyer's country	1 phase, 230 volts A.C. 50 Hz, viz. according to voltage of buyer's country	1 phase, 230 V A.C., 50 Hz or as per voltage of customer's country



### BAIER Prägetechnik

Lindentaler Str. 78  
D-73635 Rudersberg  
Tel. +49 (0) 71 83/92 71-0  
Fax +49 (0) 71 83/34 81  
E-Mail: info@hotstamping.de  
www.hotstamping.de